

DIGITAL INDICATOR

SPECIAL FEATURES :

- ⇒ Simple & Quick 4 Buttons
- ⇒ Small Size
- ⇒ 2 Set Points
- ⇒ Digital Calibration
- ⇒ 100 Samples/Sec
- ⇒ Panel Mountable
- ⇒ Peak Hold Facility



SPECIFICATIONS :

Model	:	SM - XX - X.
Resolution	:	0 - 20000 Counts.
Display	:	6 Digit Red/Green 0.56" Seven Segment LED.
Accuracy	:	$\pm 0.1\% \pm 1$ Count.
Thermal Drift	:	< 100 ppm/ $^{\circ}\text{C}$.
Excitation Voltage	:	5 V DC.
Power Supply	:	230 V, 50 Hz AC Mains.
Update Rate	:	Variable from 4 Samples/Sec to 100 Samples/Sec.
Circuitry	:	Microprocessor Based.
Relays	:	2 Nos. 5A, 230 V/50 Hz, Resistive Load.
Operating Temperature	:	0°C to 50°C .
Enclosure	:	ABS Plastic Case / Metal Enclosure.
Minimum Bridge Resistance	:	85Ω (4 off 350Ω Sensors in Parallel).
Dimensions	:	48 x 96 x 110 mm Deep.

Please Communicate to :



R.R.SENSORS & SYSTEMS.

Factory : # 17, BHADRAPPA ESTATE, MAGADI MAIN ROAD, KAMAKSHIPALYA, BANGALORE - 560079.

☎ : 080 - 23281697, E - mail : rrsensors@yahoo.com, sales@rrsensorsandsystems.com .